



Bimal Pharma Pvt. Ltd., Mumbai, India
(ISO 9001 : 2015 & AEO T1 Certified Co.)

BIMAL PHARMA PVT. LTD. MUMBAI (INDIA)	FINISHED PRODUCT INFORMATION
QUALITY CONTROL AND ASSURANCE	PRODUCT : ZINC OXIDE, CI 77947 (Cosmetic Grade)
MSDS No.: BPPL 217 (Available on Request)	SPECIFICATION No.: FP-217 (Enclosed)

1. **NOMENCLATURE** : Zinc Oxido
: Zinc White
: C.I. 77947
: C.I. Pigment White 4
2. **CAS No.** : 1314-13-2
3. **HSN CODE** : 28170010
4. **EMPIRICAL FORMULA** : ZnO
5. **MOL. WT.** : 81.39
6. **MELTING POINT** : 1975°C
7. **STRUCTURAL FORMULA** : $O=Zn$
8. **DESCRIPTION** : A Soft, White or faintly Yellowish White
Amorphous Powder, Free from Grittiness.
: It gradually absorbs Carbon Dioxide from Air.
9. **APPLICATION IN** : For high Quality Eye and Face make-ups,
Lip sticks & Sunscreen.
10. **SHELF LIFE** : 5 Years

BIMAL PHARMA PVT. LTD. MUMBAI (INDIA)	FINISHED PRODUCT SPECIFICATION
QUALITY CONTROL AND ASSURANCE	PRODUCT : ZINC OXIDE, CI 77947 (Cosmetic Grade)
MSDS No.: BPPL 217 (Available on Request)	SPECIFICATION No.: FP-217 (Enclosed)

1. **DESCRIPTION** : A Soft, White Amorphous Powder,
Free from Grittiness.
: It gradually absorbs Carbon Dioxide from Air.
2. **SOLUBILITY** : Insoluble in Water and in Ethanol (96%),
Soluble in Dilute Acids & strong bases.
3. **IDENTIFICATION** : A) It becomes Yellow when strongly heated &
The Yellow color disappears on cooling.
B) Sol. Gives the reaction of Zinc.
4. **ALKALINITY** : NMT 0.3 ml of 0.1 M HCL requires to Change
the Color of indicator
5. **CARBONATE AND
SUBSTANCES INSOLUBLE
IN ACID** : Should be pass the Prescribed Test
6. **ASSAY (on Ignited basis)** : 99.0% to 100.5%
7. **IRON** : 200 ppm Max.
8. **MERCURY** : 0.1 ppm Max.
9. **CADMIUM** : 3.0 ppm Max.
10. **ARSENIC** : 3.0 ppm Max.
11. **LEAD** : 10.0 ppm Max.

Bimal Pharma Pvt. Ltd.

www.titaniumdioxidefoodindia.com

BIMAL PHARMA PVT. LTD. MUMBAI (INDIA)	FINISHED PRODUCT SPECIFICATION
QUALITY CONTROL AND ASSURANCE	PRODUCT : ZINC OXIDE, CI 77947 (Cosmetic Grade)
MSDS No.: BPPL 217 (Available on Request)	SPECIFICATION No.: FP-217 (Enclosed)

- 12. LOSS ON IGNITION** : NMT 1.0%
(at 800 + / - 25°C Temp.)
- 13. SUBSTANCES
NOT PRECIPITATED
BY SULFIDE** : NMT 0.5 %
- 14. CONTENT OF ZINC** : 79.0% Min.
- 15. SIEVE TEST** : 98% Min. Passes through 200 Micron
- 16. MICROBIAL CONTAMINATION**
- Total Aerobic
Microbial Count** : NMT 10 cfu/gms
Yeasts and Molds : NMT 10 cfu/gms
Salmonella & E.Coli : Absent
- 17. STORAGE** : It can be stored at Room Temp. below 28°C.
: Store in the Original packing, tightly closed and
Dry in a Cool, well-ventilated place.
Away from Sunlight, heat and incompatible
materials such as Acids and bases.
- 18. PACKING** : 25 kgs. Fibre Drum with PE Liner inside.
: 25 kgs. Paper / HDPE Bag.